

## PRODUCT INFORMATION

A



### SPECIAL DESIGN

Depth of this inserts is only 35 cm, therefore they are recommended for shallow casings that save space.

### EASY INSTALLATION

Double adjustment of the feet height (smooth and step up to +14 cm).  
Cast iron out flue movable 360°.  
Possibility of changing the direction of door opening in S models.

### EASY TO OPERATE

Fireplace without grate allows cleaning with vacuum ash cleaner.  
Inserts available with a guillotine door.

### QUALITY

Insert made of high-quality P265GH boiler steel, which is resistant to continuous operation at high temperature. Reinforced door profile.  
New guillotine mechanism with service access.

### REPEATABILITY

Production use a modern machine park:  
welding robots, press brakes, laser cutters.

### ECOLOGY

Meet strict emission standards and the ECODESIGN directive, thanks to the use of afterburning system and two deflectors (steel and ceramic).

### MODERNITY

DEKOR printed glass as standard.

### SAFETY

The innovative ventilated handle protects against scalding.

### CONTROL

The built-in four-stage damper enables adjustment of the amount of air supplied

Nominal power [kW]	12,2
Heating load range [kW]	6-16
Thermal efficiency [%]	77
CO emission (by 13% O <sub>2</sub> ) [g/m <sup>3</sup> ]	0,716
Dust emission [g/m <sup>3</sup> ]	0,038
Average fuel consumption [kg/h]	3,5
Recommended active area of outlet grids [cm <sup>2</sup> ]	840-960
Recommended active area of inlet grids [cm <sup>2</sup> ]	480-780
Dimensions of the glass [mm]	590x430
External dimensions [mm]	882x1313x420
Maksimum log lenght [mm]	330
Flue diameter [mm]	160
Air intake diameter [mm]	125
Weight [kg]	210
Efficiency coefficient	102,7
Energy class	A

### ADDITIONAL OPTIONS:

masking frame 4/4

