

PRODUCT INFORMATION



ECONOMY

Attractive price thanks to simplified construction.
Available models with standard doors only.

QUALITY

Inserts made of high-quality P265GH boiler steel, which is resistant to continuous operation at high temperature.
A reinforced door profile is used.

REPEATABILITY

Production use a modern machine park:
welding robots, press brakes, laser cutters.

ECOLOGY

Inserts meet restrictive emission standards and the ECODESIGN directive, thanks to the use of afterburning system and two deflectors.

EASY OPERATION

Easy cleaning thanks to cast iron grate with a removable ash container.

CONTROL

The built-in air intake with throttle enables adjustment of the amount of fresh air supplied.

MODERNITY

Stylish black handle and printed Decor glass as standard.

Nominal power [kW]	9,0
Heating load range [kW]	4,5-11,5
Thermal efficiency [%]	80,5
CO emission (by 13% O ₂) [g/m ³]	0,717
Dust emission [g/m ³]	0,026
Average fuel consumption [kg/h]	2,7
Combustion gas temperature [°C]	249
Recommended active area of outlet grids [cm ²]	420-480
Recommended active area of inlet grids [cm ²]	240-390
Dimensions of the glass [mm]	540x390
External dimensions [mm]	662x863x458
Maksimum log lenght [mm]	300
Flue diameter [mm]	180
Air intake diameter [mm]	125
Weight [kg]	100
Efficiency coefficient	107,7
Energy class	A+

ADDITIONAL EQUIPMENT:

heat radiators, steel out flue, adjustable feet (+4 cm)

ADDITIONAL OPTIONS:

masking frame 4/4

